

# TECHNICAL SPECIFICATION

## FABRIC-BACKED VINYL WALLCOVERING

---

<b>Product</b>	Impasto Lines
<b>Description</b>	Commercial quality vinyl wallcovering laminated onto a non woven fibre backing.
<b>Weight</b>	450 grammes per square metre.
<b>Roll Size</b>	68cm x 8.2m (sold in rolls)
<b>Fire Rating</b>	Euroclass B
<b>Adhesive</b>	Generally Tekfix Plus, though depends on substrate. Tekfix VOV should be used when installing around right angled corners.
<b>Hanging</b>	<p>Apply adhesive to back of wallcovering, working right up to the edges while being careful to keep the adhesive off the patterned side. Fold or “book” each end toward the middle, pasted sides together, aligning the edges carefully so they do not dry out. Do not crease the wallcovering. Allow to soak for 10 minutes. Carefully smooth wallcovering onto wall surface using a spatula, allowing 5-10cm at top and bottom for trimming. Butt join lengths, matching pattern up. Do not reverse hang. Pattern match: 64cm vertical / half drop match.</p> <p>Remove any adhesive seepage <i>immediately</i> with detergent solution and clean water. Rinse thoroughly. Specific hanging instructions are supplied to contractor with delivery.</p>
<b>Maintenance</b>	<p>Fabric-backed vinyls offer an easy-clean finish, and high resistance to knocks and scrapes. They are designed to withstand high traffic levels, and will not tear easily. With regular cleaning they will retain their original appearance for many years depending on area of use.</p> <p>Always carry out a trial in an inconspicuous area first, to ensure cleaning agent suitable. Clean with a mild non-soapy detergent with soft cloth, sponge or soft bristle brush to prevent build up of dirt and staining. Avoid polishes and abrasive cleaning agents as they will cause build up of dirt in the surface texture, and can also damage metallic finishes. Avoid strong active solvent cleaners as they can stain and damage the vinyl surface. Always clean from the skirting level upwards. Rinse thoroughly with clean water. Individual stains should be removed as quickly as possible. This wallcovering contains antimicrobials which guard against mildew and bacterial growth.</p>
<b>Health &amp; Safety</b>	This product is classified as non-hazardous and therefore does not require any special handling. This product does not require special labelling.
<b>Handling/Storage</b>	Store at ambient temperatures away from heat source. Suitable lifting equipment may be required.
<b>Fire Fighting</b>	Any extinguishing media are suitable. Wear self contained breathing apparatus, protective clothing and full face mask. Fumes should be ventilated immediately due to possible liberation of noxious gases.
<b>Ecological</b>	This product is not bio-degradable. Dispose of in accordance with Local Authority regulations or via an authorised contractor.

---

TEKTURA  
WALLCOVERINGS

TEKTURA PLC, Suite 1.03 Harbour Island, 34 Harbour Exchange Square, London E14 9GE  
Tel 020 7536 3300 Fax 020 7536 3322