TECHNICAL SPECIFICATION FABRIC-BACKED VINYL WALLCOVERING

Product Patina Stone

DescriptionCommercial quality vinyl wallcovering laminated onto a polycotton

osnaburg backing.

Weight 450 grammes per square metre.

Roll Size 137cm x 27m

Fire Rating Euroclass C / Class 0 and 1 to BS476 part 6 and 7

Adhesive Generally Tekfix Plus, though depends on substrate. Tekfix VOV should be

used when installing around right angled corners.

Hanging Care should be taken during installation in order to produce optimum results.

Apply adhesive to wall surface. Carefully smooth wallcovering onto wall surface using a spatula, allowing 5-10cm at top and bottom for trimming. Overlap lengths, and double cut through. Run seam roller up join to ensure even adhesion. Remove any adhesive seepage *immediately* with detergent solution and clean water. Rinse thoroughly. Reverse alternate lengths. Patina Stone has

a random match.

Maintenance Fabric-backed vinyls offer an easy-clean finish, and high resistance to knocks

and scrapes. They are designed to withstand high traffic levels, and will not tear easily. With regular cleaning they will retain their original appearance for many

years depending on area of use.

Always carry out a trial in an inconspicuous area first, to ensure cleaning agent suitable. Clean with a mild non-soapy detergent with soft cloth, sponge or soft bristle brush to prevent build up of dirt and staining. Avoid polishes and abrasive cleaning agents as they will cause build up of dirt in the surface texture, and can also damage metallic finishes. Avoid strong active solvent cleaners as they can stain and damage the vinyl surface. Always clean from the skirting level

upwards. Rinse thoroughly with clean water. Individual stains should be removed as quickly as possible. This wallcovering contains antimicrobials which

guard against mildew and bacterial growth.

Health & Safety This product is classified as non-hazardous and therefore does not require

any special handling. This product does not require special labelling.

Handling/Storage Store at ambient temperatures away from heat source. Suitable lifting

equipment may be required.

Fire Fighting Any extinguishing media are suitable. Wear self contained breathing

apparatus, protective clothing and full face mask. Fumes should be ventilated immediately due to possible liberation of noxious gases.

Ecological This product is not bio-degradable. Dispose of in accordance with Local

Authority regulations or via an authorised contractor.

